



STANDARD

Test & Measuring Instruments

DIGITAL H.V. INSULATION TESTER



6211A IN


FEATURES

- Microprocessor technology ensures high performance accuracy and reliability.
- Four insulation test voltages (DC V).
- Insulation resistance, auto ranging on all ranges.
- Bargraph indicates test voltage, decay can be observed during discharge.
- Measures insulation test time.
- Display warning of external voltage.
- Fully protected : crow bar.
- Housed in heavy duty carry case.
- EEPROM calibration.
- EN/IEC 61010-1 CAT III

SPECIFICATIONS

Test Voltage (DC V)	1KV	2.5KV	5KV	10KV
Measuring Ranges (Auto-Ranges)	0-50GΩ	0-125GΩ	0-250GΩ	0-500GΩ
Accuracy	±3%rdg ±3dgt			
Output Current Limit	50uA to 100uA (1W)			
Live warning	> 500V AC			
Operating-Temperature	0°C ~ 40°C			
Operating-Humidity	85% Max. relative humidity			
Weight	3.6kg Approx.			
Dimensions	330(L) x 260(W) x 160(D)mm			
Power Source	1.5V "C" x 8 Alkaline Batteries			
Accessories	Test leads Instruction manual Batteries			

Test leads




AL-50



AL-30



AL-30C



STANDARD ELECTRIC WORKS CO., LTD.

5F.,NO.105, Jhongcheng Rd., Tucheng Dist.,
New Taipei City 23674, Taiwan (R.O.C.)

TEL: 886-2-22681528 FAX: 886-2-22681529

http://www.sew.com.tw e-mail: sales@sew.com.tw

<http://www.51082245.com/sew.htm>