

## 指針旋轉刻度鉤表

### ANALOG POTARY SCALE CLAMP METER



**ST-375**



**ST-600**



**1010 CL**

- 可量測交流電壓(AC V)交流電流(AC A)和電阻值( $\Omega$ )。
- ST-375可作量測直流電壓(DC V)。
- 採用旋轉式刻度板。
- 指針鎖定推扭設計，方便識讀。
- 1010 CL採用吊線式高品質防震表頭。

#### 選擇參考表

區分 \ 型號	ST-375	ST-600	1010 CL
交流電流(AC A)	300A	600A	1000A
交流電壓(AC V)	600V	600V	750V
直流電壓(DC V)	75V	—	—
電阻( $\Omega$ )	2k $\Omega$	2k $\Omega$	2k $\Omega$

#### ST-375

#### ST-600

#### 1010 CL

交流電流(AC A)	6/15/60/150/300A $\pm 3\%$ 滿刻度(50/60Hz)	6/30/60/300/600A $\pm 3\%$ 滿刻度(50/60Hz)	10/30/100/300/1000A $\pm 3\%$ 滿刻度(50/60Hz)
交流電壓(AC V)	300/600V $\pm 3\%$ 滿刻度	150/300/600V $\pm 3\%$ 滿刻度	150/300/750V $\pm 3\%$ 滿刻度
直流電壓(DC V)	75V $\pm 3\%$ 滿刻度	—	—
電阻( $\Omega$ )	2K $\Omega$ $\pm 3\%$ 刻度長	2K $\Omega$ $\pm 3\%$ 刻度長	2K $\Omega$ $\pm 3\%$ 刻度長
頻率適用檔位	50/60Hz : 6A 50-400Hz : 15/60/150/300A	50/60Hz : 6A 50-400Hz : 30/60/300/600A	50/60Hz : 10A 50-400Hz : 30/100/300/1000A
鉤部最大內徑	38 公厘	38 公厘	52 公厘
使用電池	1.5V(SUM-3)*1	1.5V(SUM-3)*1	1.5V(SUM-3)*1
外形尺寸	230(長)*72(寬)*37(高)公厘	230(長)*72(寬)*37(高)公厘	227(長)*73(寬)*33(高)公厘
重量	約 420 克	約 420 克	約 460 克
附件	測試線*1(組) 說明書*1(本) 軟袋*1(個)	測試線*1(組) 說明書*1(本) 軟袋*1(個)	測試線*1(組) $\Omega$ 測線*1(條) 說明書*1(本) 軟袋*1(個)
安規標準	EN 61010-1 EN 61010-2-32 CAT II 600V		—



CE

## ST-375



CE

## ST-600



## 1010CL

### FEATURES

- Designed for measuring AC current, AC voltage, resistance and DC voltage (only ST-375)
- Rotary scale which presents only one scale in windows at one time to avoid any possible reading errors.
- Pointer lock function freezes the reading in dimly lit or hard to reach places.
- $\Omega$  range ideal for checking the continuity of relays, transformers and motor coils.

- TAUT BAND movement (1010 CL)

Model	ST-375	ST-600	1010 CL
ACA	▲300A	▲600A	▲1000A
ACV	▲600V	▲600V	▲750V
DCV	▲75V	—	—
$\Omega$	▲2K $\Omega$	▲2K $\Omega$	▲2K $\Omega$
POINTER LOCK	▲	▲	▲

### SPECIFICATIONS

Model	ST-375	ST-600	1010 CL
ACA	6/15/60/150/300A ±3% of F.S.(50/60Hz)	6/30/60/300/600A ±3% of F.S.(50/60Hz)	10/30/100/300/1000A ±3% of F.S.(50/60Hz)
ACV	300/600V ±3% of F.S.	150/300/600V ±3% of F.S.	150/300/750V ±3% of F.S.
DCV	75V ±3% of F.S.	—	—
$\Omega$	2K $\Omega$ ±3% of F.S. length	2K $\Omega$ ±3% of F.S. length	2K $\Omega$ ±3% of F.S. length
Frequency Response	50/60Hz for ACA 6A 50-400Hz for ACA 15/60/150/300 A	50/60Hz for ACA 6A 50-400Hz for ACA 30/60/300/600A	50/60Hz for ACA 10A 50-400Hz for ACA 30/100/300/1000A
Dimensions	230(L) x 72(W) x 37(D)mm	230(L) x 72(W) x 37(D)mm	227(L) x 73(W) x 33(D)mm
Conductor Size	38mm Max.	38mm Max.	52mm Max.
Weight (Battery Included)	420g Approx.	420g Approx.	460g Approx.
Accessories	Test leads (AL-26) Carrying case (CAC-600) Instruction manual	Test leads (AL-26) Carrying case (CAC-600) Instruction manual	Test leads (TEL-AL11-1+OTL-1000) Ohm test probe Carrying case (CAC-600) Instruction manual
Safety Standard	EN 61010-1 EN61010-2-32 CAT II 600V	EN 61010-1 EN61010-2-32 CAT II 600V	—

STANDARD ELECTRIC WORKS CO., LTD.

5F.,NO.105, Jhongcheng Rd., Tucheng Dist.,  
New Taipei City 23674, Taiwan (R.O.C.)

TEL: 886-2-22681528 FAX: 886-2-22681529

http://www.sew.com.tw e-mail: sales@sew.com.tw

<http://www.51082245.com/sew.htm>