

指針式三用電表

MULTITESTER

ST-505N是新設計的外形，造型優美，便於把握操作，功能多樣的三用電表，是各種電氣設備、工程人員量測的最佳幫手。

特點：

1. 高品質、高感度的吊線式防震表頭。
2. 多顏色的刻度板，便於識讀。
3. 背光刻度板設計，容易判別指針的位置，方便識讀。
4. 在各檔位均作安全保護功能。
5. 有作分貝量測設計。
6. 通過歐洲安全規範獲貼"CE"。



CE

ST-505N

電氣規格：

- 直流電壓(DCV)：
0.25/1/2.5/10/50/250/1000V(±2% F.S.)
- 交流電壓(ACV)：
2.5/10/50/250/1000V(±3% F.S.)
- 直流電流(DCA)：
25µA-1mA-25mA-500mA-10A(±2% F.S.)
- 交流電流(ACA)：10A
- 阻抗(Ω)：

Rx1	0.2 Ω to 20k Ω
Rx10	2 Ω to 200k Ω
Rx100	20 Ω to 2M Ω
Rx1000	200 Ω to 20M Ω
- 使用電池：1.5V(UM-3) x 2(顆)
- 外形尺寸：160(長) x 100(寬) x 45(高)mm
- 重量：約380克(含電池)
- 配件：測試線 x 1(組)
說明書 x 1(本)
電池

ANALOG MULTITESTER

This 50kΩ/V analog multimeter with its wide range of measurement capabilities, which includes a 10A AC range, is particularly designed for the requirement of electrical and electronic specialists and engineers. This instrument is also provided with meter over load protection and shock proof device.

FEATURES

- High quality Taut Band movement.
- Easy to read 3-color scale : for mistake proof reading.
- Mirror scale : makes reading pointer easy.
- Safety features : on all ranges.
- Safety features : safety fused, safety "OFF" position.
- dB measurement.
- With stand : makes reading and measuring easy.
- IEC/EN 61010-1 : 01 CAT III 600V.
 EN 61326-1 : 06, EN 61326-2-2 : 06,
 EN 55011 : 07+A2 : 07, EN 61000-3-2 : 06,
 EN 61000-3-3 : 95+A1 : 01+A2 : 05,
 EN 61000-4-2 : 95+A1 : 98+A2 : 01,
 EN 61000-4-3 : 02+A1 : 02,
 EN 61000-4-4 : 04,
 EN 61000-4-5 : 95+A1 : 01,
 EN 61000-4-6 : 96+A1 : 01,
 EN 61000-4-11 : 04

SPECIFICATIONS

DC Voltage

Ranges	0.25/1/2.5/10/50/250/1000V
Accuracy	±2% F.S.
Sensitivity	50kΩ/V

AC Voltage

Ranges	2.5/10/50/250/1000V
Accuracy	±3% F.S.
Sensitivity	10kΩ/V
Decibelmeter	-20 to 62dB 0dB=1mW/600Ω Direct Scale : -20 to + 10dB



DC Current

Ranges	25uA-1mA-25mA/500mA, 10A(on separate input)
Accuracy	±2% F.S.
Sensitivity	250mV

AC Current

Ranges	10A
Accuracy	±3% F.S.

Resistance

Ranges	Rx1	0.2Ω to 20kΩ
	Rx10	2Ω to 200kΩ
	Rx100	20Ω to 2MΩ
	Rx1K	200Ω to 20MΩ
Accuracy	±3% of F.S. length	

General

Power Source	1.5V(UM-3, SUM-3 or R6)x2
Dimension	160(L)x100(W)x45(D)mm
Weight	380g(battery included)
Accessories	Test Leads Instruction manual Batteries